



Type Designation	4120
Designation IEC	LR20
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	15800 (discharge with high-resistance)
Permissible Temperature Range	- 10 °C ... 50 °C
Weight, approx. [g]	135,1
Volume [ccm]	51

Dimensions [mm]	min:	max:
Ø	32.3	34.2
A	-	61.5
B	59.5	-
C	18.0	-
E	-	1.0
F	-	9.5
G	1.5	-

Typical Capacities (at 20°C)



Discharge Type	Load	End Voltage[V]	0.9
4M/15M,8H/D,7D/W	2.2 Ω	Time [h]	25,8
Portable Lightings		Capacity [Ah]	13,3
		Energy [Wh]	15,3
Discharge Type	Load	End Voltage[V]	0.8
1H/D,7D/W	2.2 Ω	Time [h]	28,2
Toys		Capacity [Ah]	13,6
		Energy [Wh]	14,7
Discharge Type	Load	End Voltage[V]	0.9
4H/D,7D/W	10 Ω	Time [h]	126,7
Transistor Radios		Capacity [Ah]	15,17
		Energy [Wh]	18,32

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.